

A file with robust index

Wilberd van der Kallen



# Contents

<b>Contents</b>	<b>iii</b>
<b>Preface</b>	<b>v</b>
<b>1 Introduction</b>	<b>5</b>
<b>A Structure of the <math>\LaTeX</math> file</b>	<b>7</b>
<b>B Purpose of <code>robustindex.sty</code></b>	<b>9</b>
<b>Glossary of Notations</b>	<b>11</b>
<b>Index</b>	<b>12</b>



# Preface

This file illustrates some features of the `robustindex` package.

Although this is not a book, we have chosen the book style for illustration.

We will recall the purpose of `robustindex.sty` in appendix [B](#).

If you want to see how `robustindex.sty` may be used, compare the file `robustsample.tex` or appendix [A](#) with the output.

If you are interested in our usage of `robustglossary.sty`, you must read the source file `robustsample.tex`.

This preface has an *indexed term*. (You see this in the source file only.)



# Chapter 1

## Introduction

This introduction has another indexed term as well as the old indexed term. The page number is again 5, but now in arabic. If you index the same term twice on the same page, then one simply gets a repeat in the index. That is inherent in our method. Indeed we had to disable the implicit page range formation of `makeindex`.

Traditionally page ranges and fonts for page numbers could be done with the encapsulating construction of `makeindex`, but that construction is broken by our package. (The encapsulating construction uses the `encap` character `|` in the argument of `\index`.)

We have restored encapsulating to some extent, sufficient for common practice, but our rules are more naive than those of `makeindex`. Thus it becomes possible to have a page range as on page 12, which has several fonts in its page numbers. That is actually bad style, but this file just illustrates features.

See the file `robustsample.tex` for details.

Subentries are still supported. We illustrate this in `robustsample.tex` and appendix A with alpha, beta and gamma. This also illustrates the use of `\gobblepageref`.

After running  $\LaTeX$  on *filename* one must run `makeindex` on *filename* to get the index entries in *filename.ind*. Before this there may be error messages about labels or names. Do not exclude any relevant files. For instance, do not use `\includeonly`.

Say we wish the index to occur in the table of contents. We then give the command `\indexincontents` before the index.

The package `hyperref` may break our code. Therefore one must use the option `hyperindex=false`, as in `\usepackage[hyperindex=false]{hyperref}`. Note that `robustindex` already puts hyperlinks in the index. Alternatively one may go against the advice of `hyperref` and put `robustindex` later in the preamble. In the file `robustsample.tex` we actually used `\usepackage[plainpages=false,hyperindex=false]{hyperref}` because of the roman page numbers in the beginning.





# Appendix A

## Structure of the L<sup>A</sup>T<sub>E</sub>X file

```
\documentclass{book}

\usepackage{makeidx}
\usepackage{robustindex}
\usepackage[plainpages=false,hyperindex=false]{hyperref}
...
...\author{Wilberd van der Kallen\index{Wilberd}}
...
\makeindex    % obligatory with robustindex

\begin{document}
...
\tableofcontents
...\index{indexed term}                % on page v
...\index{other term!cited twice on same page} % on page 5
...\index{indexed term}                % on page 5
...\index{other term!cited twice on same page} % on page 5
...
\index{alpha!see beta}                  % on page 5
\index{alpha!see also gamma\gobblepageref} % on page 5
...
% For special effects you could simply edit filename.ind
% We illustrate our poor man's encapsulation.
\index{...|...}...                      % on page 6
\index{...|...}...                      % on page 7
\index{...|...}...                      % on page 9
....
\indexincontents % before the index.
\printindex

\end{document}
```



## Appendix B

# Purpose of `robustindex.sty`

Amazingly often a third party changes the page numbers without rerunning `makeindex`. It is much nicer to have an index that adapts itself to all changes that do not involve `\index{entry}` commands.

The package achieves this by invoking the `\pageref` mechanism on automatically generated labels of the form `ind.2`, `ind.4`, `...`

Only after adding/deleting/modifying an `\index{entry}` command, or after changing the order of `\index{entry}` commands, does one have to run `makeindex`. But then it is important that you do run `makeindex`, even when no warning is issued. The robustness has its limits.



# Glossary of Notations

$H^0(X, \mathcal{L})$  the sections of the vector bundle  $\mathcal{L}|_X$  over  $X$ , **5**  
 $\text{Ext}_B^i(M, N)$  Ext group in the category  $\mathcal{C}_B$ , **v**

# Index

- alpha
  - see also gamma
  - see beta, 5
- indexed term, v, 5
- other term
  - cited twice on same page, 5, 5
- page range, 5–9
  - this |is| complicated, 5–8, 9
  - with risky label, 9
- simpler
  - page range, 5–9
- simplest page range, 5–9
- Wilberd, i